

屋内照明器具特性

品番 (品名)	NNF 23107J	
光源	LED5000_70_115 ×1	115.0 lm
管理番号	K0169873(0)DR1	
BZ分類	BZ1	

器具効率	100%	反射率	天井 80%				70%				50%				30%				0%			
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10				
上方光束	0%		10%				10%				10%				10%				0%			
下方光束	100%		室指数																			
			照明率 (X0.01)																			
			ZCM																			
保守率	良 0.69	0.6	78	71	66	63	77	71	66	63	76	70	66	63	75	69	65	63	62			
	中 0.67	0.8	85	78	73	70	84	77	73	70	82	76	72	69	80	75	72	69	68			
	否 0.63	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	76	74	72			
下方投影面積	cm ²	1.25	92	87	83	79	91	86	82	79	89	85	81	79	87	84	81	78	77			
		1.5	95	90	86	83	94	89	86	83	92	88	85	82	90	86	84	81	80			
等価発光面積	cm ²	2.0	98	94	91	88	97	93	90	88	95	92	89	87	93	90	88	86	84			
		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	93	91	89	87			
取付高さ	器具間隔最大限		3.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89		
	横方向 (A)	縦方向 (B)	4.0	103	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94	91		
Hm	0.36Hm	0.36Hm	5.0	104	103	101	99	103	101	100	99	101	100	98	97	99	98	97	96	93		
			7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95		
			10.0	106	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	97		

