

# 屋内照明器具特性

品番 (品名) **LGB15336**

光源 **LLD2020LCE1 x1** **460.0 1m**

管理番号 **K0176317(0)DR1**

BZ分類 **BZ1**

器具効率	93%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	93%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X 0.01 )																ZCM	
保守率	良 0.67	0.6	78	72	69	66	77	72	68	66	76	71	68	66	75	71	68	66	65	
	中 0.63	0.8	84	78	75	72	83	78	75	72	81	77	74	72	80	76	74	72	71	
	否 0.56	1.0	87	82	79	77	86	82	79	76	85	81	78	76	83	80	78	76	75	
下方投影面積	cm <sup>2</sup>	1.25	90	86	83	80	89	85	82	80	87	84	82	80	86	83	81	79	78	
		1.5	92	88	85	83	91	87	85	83	89	86	84	82	87	85	83	82	80	
等価発光面積	cm <sup>2</sup>	2.0	94	91	89	87	93	90	88	86	91	89	87	86	90	88	86	85	83	
		2.5	96	93	91	89	95	92	90	89	93	91	89	88	91	89	88	87	85	
取付高さ	器具間隔最大限		3.0	97	94	93	91	95	94	92	90	94	92	91	89	92	90	89	88	
Hm	0.41Hm	0.41Hm	4.0	98	96	95	93	97	95	94	93	95	93	92	91	93	92	91	90	88
			5.0	98	97	96	95	97	96	95	94	95	94	93	93	93	93	93	92	91
			7.0	99	98	97	96	98	97	96	96	96	95	95	94	94	94	93	92	90
			10.0	100	99	98	98	99	98	97	97	97	96	96	95	95	94	94	93	91

