

# 屋内照明器具特性

|         |                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB15336               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD2000CU1 x1 566.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0179050(0)DR1         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ3/4.5/BZ4            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |      |             |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |
|--------|------------------|---------|------|-------------|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|----|
| 器具効率   | 80%              | 天井      | 80%  |             |     |    | 70% |    |     |    | 50% |    |     |    | 30% |    |     |    | 0% |    |
|        | 上方光束<br>1%       |         | 反射率  | 70          | 50  | 30 | 10  | 70 | 50  | 30 | 10  | 70 | 50  | 30 | 10  | 70 | 50  | 30 | 10 | 0% |
|        |                  |         |      | 下方光束<br>79% | 10% |    |     |    | 10% |    |     |    | 10% |    |     |    | 10% |    |    |    |
| 室指数    | 照明率 ( X0.01) ZCM |         |      |             |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |
| 保守率    | 良                | 0.67    | 0.6  | 51          | 43  | 38 | 34  | 50 | 43  | 38 | 34  | 49 | 42  | 37 | 34  | 47 | 41  | 37 | 34 | 32 |
|        | 中                | 0.63    | 0.8  | 59          | 51  | 46 | 42  | 58 | 50  | 45 | 42  | 56 | 49  | 45 | 41  | 54 | 48  | 44 | 41 | 40 |
|        | 否                | 0.56    | 1.0  | 63          | 56  | 51 | 47  | 62 | 55  | 51 | 47  | 60 | 54  | 50 | 47  | 58 | 53  | 49 | 46 | 45 |
|        |                  |         | 1.25 | 67          | 61  | 56 | 52  | 66 | 60  | 56 | 52  | 64 | 59  | 55 | 52  | 62 | 58  | 54 | 51 | 50 |
| 下方投影面積 |                  |         | 1.5  | 70          | 64  | 60 | 56  | 69 | 63  | 59 | 56  | 67 | 62  | 58 | 55  | 65 | 61  | 57 | 55 | 53 |
|        | 等価発光面積           |         | 2.0  | 74          | 69  | 65 | 62  | 73 | 68  | 64 | 61  | 70 | 67  | 63 | 61  | 68 | 65  | 62 | 60 | 58 |
| 取付高さ   | 器具間隔最大限          |         | 2.5  | 76          | 72  | 68 | 65  | 75 | 71  | 68 | 65  | 73 | 69  | 67 | 64  | 71 | 68  | 66 | 63 | 62 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0  | 78          | 74  | 71 | 68  | 76 | 73  | 70 | 68  | 74 | 72  | 69 | 67  | 72 | 70  | 68 | 66 | 64 |
| Hm     | 1.32Hm           | 1.32Hm  | 4.0  | 80          | 77  | 74 | 72  | 79 | 76  | 74 | 71  | 76 | 74  | 72 | 70  | 74 | 73  | 71 | 69 | 67 |
|        |                  |         | 5.0  | 81          | 79  | 76 | 74  | 80 | 78  | 76 | 74  | 78 | 76  | 74 | 73  | 76 | 74  | 73 | 72 | 69 |
|        |                  |         | 7.0  | 82          | 81  | 79 | 77  | 81 | 80  | 78 | 77  | 79 | 78  | 77 | 75  | 77 | 76  | 75 | 74 | 72 |
|        |                  |         | 10.0 | 83          | 82  | 81 | 80  | 82 | 81  | 80 | 79  | 80 | 79  | 79 | 78  | 79 | 78  | 77 | 76 | 74 |

