

屋内照明器具特性	
品番 (品名)	NNF 4 1 5 1 8 J
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1m
管理番号	K0127795(1)DB1
BZ分類	BZ5

器具効率	93%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	51	40	32	27	50	39	32	27	48	38	31	27	46	37	31	27	25
	中	0.77	0.8	61	50	42	37	59	49	42	37	57	48	41	37	54	47	41	36	34
	否	0.68	1.0	67	57	50	44	66	56	49	44	63	55	48	44	60	53	48	43	41
			1.25	73	64	57	51	71	63	56	51	68	61	55	51	66	59	54	50	48
下方投影面積		cm <sup>2</sup>	1.5	77	68	62	57	75	67	61	56	72	66	60	56	70	64	59	55	53
等価発光面積		cm <sup>2</sup>	2.0	82	75	69	64	81	74	69	64	78	72	67	63	75	70	66	63	60
取付高さ	器具間隔最大限		2.5	85	79	74	70	84	78	74	69	81	76	72	69	78	74	71	68	65
	横方向 (A)	縦方向 (B)	3.0	88	83	78	74	86	81	77	73	83	79	76	72	81	77	74	71	69
1.5m	1.69m	2.16m	4.0	91	87	83	79	89	85	82	79	87	83	80	78	84	81	79	76	74
2	2.24	2.73	5.0	93	89	86	83	91	88	85	82	89	86	83	81	86	84	82	80	77
2.5	2.78	3.31	7.0	95	92	90	87	93	91	89	87	91	89	87	85	88	87	85	84	81
3	3.33	3.91	10.0	96	94	93	91	95	93	92	90	93	91	90	88	90	89	88	87	84

