

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 7 6
光源	LED_FULL4000_85_4550 ×1 4550.0 1 m
管理番号	K0135881 (0) DB 1
BZ分類	BZ4 / 0.7 / BZ3 / 8.5 / BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	63 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	37 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	50	39	32	28	45	36	30	26	37	30	26	22	29	25	21	19	13
	中	0.81	0.8	59	48	42	37	53	45	39	34	44	37	33	29	35	30	27	25	17
	否	0.77	1.0	64	55	49	44	59	51	45	41	48	42	38	35	38	34	31	29	20
			1.25	70	61	55	50	64	56	51	47	52	47	43	40	41	38	35	33	22
下方投影面積		c m ²	1.5	73	66	60	55	67	60	55	51	55	50	46	43	44	40	38	36	24
等価発光面積		c m ²	2.0	78	72	67	63	71	66	62	58	58	55	52	49	46	44	42	40	27
取付高さ	器具間隔最大限		2.5	81	76	71	68	74	70	66	62	61	58	55	52	48	46	44	43	28
	横方向 (A)	縦方向 (B)	3.0	83	79	75	71	76	72	69	66	63	60	57	55	50	48	46	45	29
1.5m	1.25 m	2.04 m	4.0	86	82	79	76	79	76	73	70	65	62	60	59	51	50	49	47	31
2	1.66	2.62	5.0	88	85	82	79	80	78	75	73	66	64	62	61	52	51	50	49	32
2.5	2.07	3.24	7.0	90	87	85	83	82	80	78	77	67	66	65	64	54	53	52	51	33
3	2.49	3.85	10.0	91	89	88	86	83	82	81	79	69	68	67	66	55	54	53	53	34

