

# 屋内照明器具特性

品番 (品名)	LGB16746				
光源	LLD2000CU1 x1 566.0 lm				
管理番号	K0179050(0)DR1				
BZ分類	BZ3/4.5/BZ4				

器具効率	80%	天井	80%				70%				50%				30%				0%																																									
	上方光束 1%		下方光束 79%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
				壁	10%				10%				10%				10%				0%																																							
床	室指数																				照明率 ( X0.01 )																				ZCM																			
保守率	良	0.67	0.6	51	43	38	34	50	43	38	34	49	42	37	34	47	41	37	34	32																																								
	中	0.63	0.8	59	51	46	42	58	50	45	42	56	49	45	41	54	48	44	41	40																																								
	否	0.56	1.0	63	56	51	47	62	55	51	47	60	54	50	47	58	53	49	46	45																																								
			1.25	67	61	56	52	66	60	56	52	64	59	55	52	62	58	54	51	50																																								
下方投影面積	cm <sup>2</sup>		1.5	70	64	60	56	69	63	59	56	67	62	58	55	65	61	57	55	53																																								
	等価発光面積		2.0	74	69	65	62	73	68	64	61	70	67	63	61	68	65	62	60	58																																								
取付高さ	器具間隔最大限		2.5	76	72	68	65	75	71	68	65	73	69	67	64	71	68	66	63	62																																								
	横方向 (A)	縦方向 (B)	3.0	78	74	71	68	76	73	70	68	74	72	69	67	72	70	68	66	64																																								
Hm	1.32Hm	1.32Hm	4.0	80	77	74	72	79	76	74	71	76	74	72	70	74	73	71	69	67																																								
			5.0	81	79	76	74	80	78	76	74	78	76	74	73	76	74	73	72	69																																								
			7.0	82	81	79	77	81	80	78	77	79	78	77	75	77	76	75	74	72																																								
			10.0	83	82	81	80	82	81	80	79	80	79	79	78	79	78	77	76	74																																								

