

屋内照明器具特性	
品番 (品名)	XAS1502
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0178921 (0) DR1
BZ分類	BZ4

器具効率		92 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	54	43	36	32	53	43	36	31	51	42	36	31	49	41	35	31	29
			0.63	0.8	64	54	47	42	62	53	46	42	60	52	46	41	58	50	45	41	39
			0.56	1.0	70	61	54	49	68	60	54	49	66	58	53	48	63	57	52	48	46
				1.25	75	67	61	56	74	66	60	56	71	65	59	55	69	63	59	55	53
下方投影面積 等価発光面積		cm ² cm ²		1.5	79	71	66	61	77	71	65	61	75	69	64	60	72	67	63	60	58
				2.0	84	78	73	69	82	77	72	68	80	75	71	68	77	73	70	67	65
				2.5	87	82	77	74	85	81	77	73	83	79	75	72	80	77	74	71	69
				3.0	89	84	81	77	88	83	80	77	85	82	78	76	83	80	77	75	72
Hm	1.29Hm	1.29Hm		4.0	92	88	85	82	90	87	84	82	88	85	83	80	85	83	81	79	77
				5.0	93	90	88	85	92	89	87	85	89	87	85	83	87	85	84	82	79
				7.0	95	93	91	89	94	92	90	88	91	90	88	87	89	88	86	85	83
				10.0	96	95	93	92	95	94	92	91	93	92	90	89	91	90	89	88	85

