

屋内照明器具特性	
品番 (品名)	XAS1022
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0178924 (0) DR 1
BZ分類	BZ1

器具効率		98 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		98 %																							
保守率		良	0.67	0.6	82	76	72	69	81	75	71	69	80	75	71	69	78	74	71	69	68				
		中	0.63	0.8	87	82	78	75	87	81	78	75	85	81	77	75	84	80	77	75	74				
		否	0.56	1.0	91	86	82	80	90	85	82	80	88	84	81	79	87	83	81	79	77				
				1.25	94	90	86	84	93	89	86	83	91	88	85	83	90	87	84	82	81				
下方投影面積		c m ²		1.5	96	92	89	87	95	91	89	86	93	90	88	86	92	89	87	85	84				
		c m ²		2.0	99	96	93	91	98	95	92	90	96	93	91	89	94	92	90	89	87				
取付高さ	器具間隔最大限			2.5	100	98	95	93	99	97	95	93	97	95	93	92	95	94	92	91	89				
	横方向 (A)		縦方向 (B)	3.0	101	99	97	95	100	98	96	95	98	96	95	94	96	95	94	92	90				
H m	0.34 H m		0.34 H m	4.0	103	101	99	98	102	100	98	97	99	98	97	96	98	96	95	94	92				
				5.0	103	102	101	99	102	101	100	99	100	99	98	97	98	97	96	96	93				
				7.0	104	103	102	101	103	102	101	100	101	100	99	99	99	98	98	97	95				
				10.0	105	104	103	103	104	103	102	102	102	101	101	100	100	99	99	98	96				

