

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 8 7
光源	LED_BASE3500_85_3050 ×1 3050.0 1m
管理番号	K0157494 (0) DB 1
BZ分類	BZ2/1.8/BZ3/3.5/BZ4/6.0/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		100%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	0%	床	10%				10%				10%				10%				0%	
室指数		照明率 ( X0.01 ) ZCM																		
保守率	良	0.83	0.6	43	33	26	22	37	28	23	19	25	20	16	13	14	11	9	8	0
	中	0.81	0.8	51	41	34	29	43	35	30	26	30	24	21	18	17	14	12	11	0
	否	0.77	1.0	57	47	41	36	48	41	35	31	33	28	25	22	19	16	14	13	0
			1.25	62	53	47	42	53	46	40	36	36	32	28	26	21	18	17	15	0
下方投影面積		cm <sup>2</sup>	1.5	65	57	51	47	56	50	45	41	38	34	31	29	22	20	18	17	0
等価発光面積		cm <sup>2</sup>	2.0	70	64	58	54	60	55	51	47	41	38	35	33	24	22	21	20	0
取付高さ	器具間隔最大限		2.5	73	68	63	59	63	58	55	51	43	41	38	36	25	24	22	21	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	63	65	61	57	54	45	42	40	38	26	25	24	23	0
1.5m	1.8m	1.73m	4.0	78	74	71	68	67	64	61	59	46	45	43	41	27	26	25	24	0
2	2.4	2.22	5.0	80	76	74	71	69	66	64	62	48	46	45	43	28	27	26	26	0
2.5	2.99	2.8	7.0	82	79	77	75	70	69	67	65	49	48	47	46	29	28	27	27	0
3	3.58	3.37	10.0	83	81	80	78	72	70	69	68	50	49	48	48	29	29	28	28	0

