

# 屋内照明器具特性

品番 (品名)	LGB16749				
光源	LLD4000LCE1 ×1                      845.0 l m				
管理番号	K0176308 ( 0 ) DR 1				
BZ分類	BZ3				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM	
下方光束	83 %																			
保守率	良 中 否	0.67	0.6	5.4	4.6	4.1	3.7	5.3	4.6	4.0	3.7	5.2	4.5	4.0	3.7	5.0	4.4	4.0	3.6	3.5
		0.63	0.8	6.2	5.5	4.9	4.6	6.1	5.4	4.9	4.5	5.9	5.3	4.9	4.5	5.8	5.2	4.8	4.5	4.4
			1.0	6.7	6.0	5.5	5.1	6.6	6.0	5.5	5.1	6.4	5.8	5.4	5.1	6.2	5.7	5.4	5.1	4.9
		0.56	1.25	7.1	6.5	6.1	5.7	7.0	6.5	6.0	5.7	6.8	6.3	5.9	5.6	6.6	6.2	5.9	5.6	5.4
下方投影面積	c m <sup>2</sup>	1.5	7.4	6.9	6.4	6.1	7.3	6.8	6.4	6.1	7.1	6.7	6.3	6.0	6.9	6.5	6.2	6.0	5.8	
		2.0	7.8	7.3	7.0	6.6	7.7	7.3	6.9	6.6	7.5	7.1	6.8	6.5	7.3	7.0	6.7	6.5	6.3	
取付高さ	器具間隔最大限		2.5	8.0	7.6	7.3	7.0	7.9	7.5	7.2	7.0	7.7	7.4	7.1	6.9	7.5	7.2	7.0	6.8	6.6
	横方向 (A)	縦方向 (B)	3.0	8.2	7.8	7.5	7.3	8.1	7.7	7.5	7.2	7.8	7.6	7.4	7.1	7.6	7.4	7.2	7.1	6.9
H m	1.39 H m	1.39 H m	4.0	8.4	8.1	7.9	7.7	8.3	8.0	7.8	7.6	8.0	7.8	7.7	7.5	7.8	7.7	7.5	7.4	7.2
			5.0	8.5	8.3	8.1	7.9	8.4	8.2	8.0	7.8	8.2	8.0	7.8	7.7	8.0	7.8	7.7	7.6	7.4
			7.0	8.6	8.5	8.3	8.2	8.5	8.4	8.2	8.1	8.3	8.2	8.1	8.0	8.1	8.0	7.9	7.8	7.6
			10.0	8.7	8.6	8.5	8.4	8.6	8.5	8.4	8.3	8.4	8.3	8.2	8.2	8.2	8.1	8.1	8.0	7.8

