

屋内照明器具特性

品番 (品名) **LGB16749**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176315(0)DR1**

BZ分類 **BZ1**

器具効率	87%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	87%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	72	67	64	61	72	67	63	61	71	66	63	61	70	66	63	61	60	
	中 0.63	0.8	78	73	70	67	77	72	69	67	76	72	69	67	74	71	69	67	66	
	否 0.56	1.0	81	76	73	71	80	76	73	71	79	75	73	71	77	74	72	70	69	
下方投影面積	cm ²	1.25	83	80	77	75	83	79	76	74	81	78	76	74	80	77	75	74	72	
		1.5	85	82	79	77	84	81	79	77	83	80	78	76	81	79	77	76	74	
等価発光面積	cm ²	2.0	87	85	82	81	86	84	82	80	85	83	81	79	83	81	80	79	77	
		2.5	89	86	84	83	88	86	84	82	86	84	83	81	84	83	82	81	79	
取付高さ	器具間隔最大限		3.0	90	88	86	84	89	87	85	84	87	85	84	83	85	84	83	82	80
	横方向 (A)	縦方向 (B)	4.0	91	89	88	87	90	88	87	86	88	87	86	85	86	85	84	84	82
Hm	0.41Hm	0.41Hm	5.0	91	90	89	88	90	89	88	87	89	88	87	86	87	86	85	85	83
			7.0	92	91	90	89	91	90	89	89	89	89	89	88	87	87	87	86	86
			10.0	93	92	91	91	92	91	90	90	90	89	89	88	88	88	87	87	84

