

屋内照明器具特性

品番 (品名)	LGB16749														
光源	LLD40001CQ1 ×1 845.0 lm														
管理番号	K0176312(0)DR1														
BZ分類	BZ3														

器具効率	76%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%	室指数																		
下方光束	76%	照明率 (×0.01)																		
		ZCM																		
保守率	良 中 否	0.67	0.6	5.0	4.2	3.7	3.4	4.9	4.2	3.7	3.4	4.7	4.1	3.7	3.3	4.6	4.0	3.6	3.3	3.2
		0.63	0.8	5.7	5.0	4.5	4.2	5.6	4.9	4.5	4.1	5.4	4.8	4.4	4.1	5.3	4.8	4.4	4.1	4.0
		0.56	1.0	6.1	5.5	5.0	4.7	6.0	5.5	5.0	4.7	5.9	5.3	5.0	4.7	5.7	5.2	4.9	4.6	4.5
			1.25	6.5	6.0	5.5	5.2	6.4	5.9	5.5	5.2	6.2	5.8	5.4	5.1	6.1	5.7	5.4	5.1	5.0
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	7.3	7.0	6.7	6.4	7.2	6.9	6.6	6.4	7.0	6.7	6.5	6.3	6.8	6.6	6.4	6.2	6.0
	横方向 (A)	縦方向 (B)	3.0	7.5	7.2	6.9	6.7	7.4	7.1	6.8	6.6	7.2	6.9	6.7	6.5	7.0	6.8	6.6	6.4	6.3
Hm	1.39Hm	1.39Hm	4.0	7.6	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.4	7.2	7.0	6.8	7.2	7.0	6.9	6.7	6.5
			5.0	7.8	7.6	7.4	7.2	7.7	7.5	7.3	7.1	7.5	7.3	7.2	7.0	7.3	7.2	7.0	6.9	6.7
			7.0	7.9	7.7	7.6	7.5	7.8	7.6	7.5	7.4	7.6	7.5	7.4	7.3	7.4	7.3	7.2	7.1	6.9
			10.0	8.0	7.9	7.8	7.7	7.9	7.8	7.7	7.6	7.7	7.6	7.5	7.5	7.5	7.4	7.4	7.3	7.1

