

# 屋内照明器具特性

品番 (品名)	NLG86465														
光源	LDS110V36W.W.K ×1 336.0lm														
管理番号	K0173123(0)DB1														
BZ分類	BZ9/0.9/BZ8														

器具効率	62%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	31%	反射率	壁	10%				10%				10%				10%				0%
下方光束	31%		床	10%				10%				10%				10%				0%
室指数		照明率 (X0.01)																		
保守率	良 0.77 中 0.72 否 0.67	0.6	2.7	2.0	1.5	1.1	2.5	1.8	1.4	1.0	2.0	1.5	1.1	9	1.6	1.2	9	7	4	
		0.8	3.2	2.5	2.0	1.6	3.0	2.3	1.8	1.5	2.4	1.9	1.5	1.2	1.9	1.5	1.2	1.0	6	
		1.0	3.6	2.9	2.4	2.0	3.3	2.6	2.2	1.8	2.7	2.2	1.8	1.5	2.2	1.8	1.5	1.2	7	
		1.25	4.0	3.3	2.8	2.4	3.6	3.0	2.5	2.2	3.0	2.5	2.1	1.8	2.4	2.0	1.7	1.5	9	
下方投影面積	cm <sup>2</sup>	1.5	4.2	3.6	3.1	2.7	3.8	3.3	2.8	2.5	3.2	2.7	2.4	2.1	2.6	2.2	1.9	1.7	1.1	
等価発光面積	cm <sup>2</sup>	2.0	4.6	4.0	3.5	3.2	4.2	3.7	3.3	2.9	3.5	3.1	2.8	2.5	2.8	2.5	2.3	2.0	1.3	
取付高さ	器具間隔最大限		2.5	4.8	4.3	3.9	3.5	4.4	4.0	3.6	3.3	3.7	3.3	3.0	2.8	3.0	2.7	2.5	2.3	1.5
	横方向 (A)	縦方向 (B)	3.0	4.9	4.5	4.1	3.8	4.5	4.2	3.8	3.5	3.8	3.5	3.2	3.0	3.1	2.9	2.7	2.5	1.7
Hm	1.77Hm	1.81Hm	4.0	5.2	4.8	4.5	4.2	4.8	4.4	4.1	3.9	4.0	3.7	3.5	3.3	3.1	2.9	2.7	1.9	
			5.0	5.3	5.0	4.7	4.4	4.9	4.6	4.4	4.1	4.1	3.9	3.7	3.5	3.4	3.2	3.1	2.0	
			7.0	5.5	5.2	5.0	4.8	5.1	4.8	4.6	4.4	4.3	4.1	3.9	3.8	3.5	3.4	3.3	2.2	
			10.0	5.6	5.4	5.2	5.1	5.2	5.0	4.9	4.7	4.4	4.3	4.2	4.0	3.7	3.6	3.5	2.4	

