

屋内照明器具特性

品番 (品名)	LGB10828	
光源	LLD4000LCE1 ×1	845.0 lm
管理番号	K0176299(0)DR1	
BZ分類	BZ2	

器具効率	53%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		53%		床	10%				10%				10%				10%			
室指数	照明率 (×0.01)																				ZCM
保守率	良	0.67	0.6	3.5	3.0	2.7	2.4	3.5	3.0	2.7	2.4	3.4	2.9	2.6	2.4	3.3	2.9	2.6	2.4	2.3	
	中	0.63	0.8	4.1	3.6	3.3	3.1	4.0	3.6	3.3	3.1	3.9	3.5	3.3	3.1	3.8	3.5	3.2	3.0	3.0	
	否	0.56	1.0	4.4	4.0	3.7	3.5	4.4	4.0	3.7	3.5	4.2	3.9	3.7	3.5	4.1	3.8	3.6	3.5	3.4	
			1.25	4.7	4.3	4.1	3.9	4.6	4.3	4.0	3.8	4.5	4.2	4.0	3.8	4.4	4.1	4.0	3.8	3.7	
下方投影面積	cm ²		1.5	4.9	4.6	4.3	4.1	4.8	4.5	4.3	4.1	4.7	4.4	4.2	4.1	4.6	4.3	4.2	4.0	3.9	
等価発光面積	cm ²		2.0	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.4	4.8	4.6	4.5	4.3	4.2	
取付高さ	器具間隔最大限		2.5	5.2	5.0	4.8	4.7	5.2	5.0	4.8	4.6	5.0	4.9	4.7	4.6	4.9	4.8	4.6	4.5	4.4	
	横方向 (A)	縦方向 (B)	3.0	5.3	5.1	5.0	4.8	5.2	5.1	4.9	4.8	5.1	5.0	4.8	4.7	5.0	4.9	4.8	4.7	4.5	
Hm	1.28Hm	1.28Hm	4.0	5.4	5.3	5.1	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.9	4.7	
			5.0	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.3	5.2	5.1	5.0	5.2	5.1	5.0	5.0	4.8	
			7.0	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.3	5.4	5.3	5.2	5.2	5.3	5.2	5.1	5.1	5.0	
			10.0	5.6	5.6	5.5	5.4	5.6	5.5	5.4	5.4	5.4	5.4	5.3	5.3	5.3	5.3	5.2	5.2	5.0	

