

屋内照明器具特性

品番 (品名)	LGB10820														
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m														
管理番号	K0184484 (0) DR1														
BZ分類	BZ4/1.4/BZ3														

器具効率	73%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 73%	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																			
保守率	良	0.67	0.6	43	35	29	25	42	34	29	25	41	34	29	25	39	33	28	25	24
	中	0.63	0.8	51	43	38	34	50	43	38	34	48	42	37	34	47	41	37	34	32
	否	0.56	1.0	56	49	44	40	55	49	44	40	53	47	43	40	51	46	43	40	38
			1.25	61	55	50	46	60	54	49	46	58	53	49	46	56	52	48	45	44
下方投影面積			c m ²																	
			c m ²																	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.30 H m	1.30 H m	4.0	74	71	69	67	73	70	68	66	71	69	67	65	69	67	66	64	63
			5.0	75	73	71	69	74	72	70	69	72	70	69	67	70	69	68	66	65
			7.0	76	75	73	72	75	74	72	71	73	72	71	70	72	71	70	69	67
			10.0	77	76	75	74	76	75	74	73	74	74	73	72	73	72	71	71	69

