

屋内照明器具特性

品番 (品名)	XAS7312L														
光源	LED2700_70_1115 x1 1115.0 lm														
管理番号	K0171369(0)D 1														
BZ分類	BZ5/0.7/BZ4/2.3/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	44%	室指数	床	10%				10%				10%				10%				0%
下方光束	56%		照明率 (X0.01) ZCM																	
保守率	良 中 否 0.67 0.63 0.56	0.6	5.2	4.0	3.3	2.8	4.8	3.8	3.2	2.7	4.2	3.4	2.8	2.4	3.6	2.9	2.5	2.2	1.7	
		0.8	6.1	5.0	4.3	3.8	5.6	4.7	4.1	3.6	4.9	4.2	3.6	3.2	4.2	3.6	3.2	2.9	2.3	
		1.0	6.7	5.7	5.0	4.4	6.2	5.4	4.7	4.2	5.4	4.7	4.2	3.8	4.6	4.1	3.7	3.4	2.7	
		1.25	7.2	6.3	5.6	5.1	6.7	5.9	5.3	4.9	5.8	5.2	4.8	4.4	5.0	4.5	4.2	3.9	3.1	
下方投影面積	c m ²	1.5	7.6	6.8	6.1	5.6	7.1	6.4	5.8	5.3	6.1	5.6	5.1	4.8	5.3	4.9	4.5	4.2	3.3	
		2.0	8.1	7.4	6.8	6.4	7.6	7.0	6.5	6.0	6.6	6.1	5.7	5.4	5.6	5.3	5.0	4.7	3.7	
取付高さ	器具間隔最大限		2.5	8.4	7.8	7.3	6.9	7.9	7.3	6.9	6.5	6.8	6.4	6.1	5.8	5.9	5.6	5.3	4.0	
	横方向 (A)	縦方向 (B)	3.0	8.6	8.1	7.7	7.3	8.1	7.6	7.2	6.9	7.0	6.7	6.4	6.1	6.0	5.8	5.6	4.2	
H m	1.28 H m	1.28 H m	4.0	8.9	8.5	8.1	7.8	8.4	8.0	7.7	7.4	7.3	7.0	6.7	6.5	6.3	6.0	5.9	4.5	
			5.0	9.1	8.7	8.4	8.1	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.4	6.2	6.1	5.9	4.6
			7.0	9.3	9.0	8.8	8.5	8.7	8.5	8.3	8.1	7.6	7.4	7.3	7.1	6.6	6.4	6.3	4.8	
			10.0	9.5	9.3	9.1	8.9	8.9	8.7	8.5	8.4	7.8	7.6	7.5	7.4	6.7	6.6	6.5	5.0	

