

# 屋内照明器具特性

品番 (品名)	LGB16121				
光源	LLD4000LCB1 ×1		845.0 lm		
管理番号	K0176281(0)DR1				
BZ分類	BZ5/0.7/BZ4/6.0/BZ3				

器具効率	64%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床		10%		10%		10%		10%		10%		10%		10%		0%	
下方光束	64%		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.67 0.63 0.56	0.6	37	30	25	21	36	29	25	21	35	29	24	21	34	28	24	21	20	
		0.8	44	37	32	29	43	36	32	29	41	36	31	28	40	35	31	28	27	
		1.0	48	42	37	34	47	41	37	34	46	40	36	33	44	39	36	33	32	
		1.25	52	47	42	39	51	46	42	39	49	45	41	39	48	44	41	38	37	
下方投影面積	c m <sup>2</sup>	1.5	55	50	46	43	54	49	46	43	52	48	45	42	50	47	44	42	40	
		2.0	59	54	51	48	58	54	51	48	56	52	50	47	54	51	49	47	45	
取付高さ	器具間隔最大限		2.5	61	57	54	52	60	57	54	51	58	55	53	51	56	54	52	50	49
	横方向 (A)	縦方向 (B)	3.0	62	59	57	54	61	58	56	54	59	57	55	53	58	56	54	53	51
H m	1.28 H m	1.28 H m	4.0	64	62	60	58	63	61	59	57	61	59	58	56	60	58	57	56	54
			5.0	65	63	61	60	64	62	61	59	62	61	60	58	61	60	58	57	56
			7.0	66	65	63	62	65	64	63	62	64	63	62	61	62	61	60	60	58
			10.0	67	66	65	64	66	65	64	64	65	64	63	62	63	62	62	61	59

