

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 0 K
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 8 9 3 1 (0) D R 1
B Z 分類	B Z 4 / 1 . 4 / B Z 3

器具効率		8 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 3	3 6	3 2	5 2	4 2	3 6	3 2	5 0	4 1	3 6	3 2	4 8	4 0	3 5	3 1	3 0
			0 . 6 3	0 . 8	6 2	5 3	4 6	4 2	6 1	5 2	4 6	4 2	5 9	5 1	4 5	4 1	5 6	5 0	4 5	4 1	3 9
			0 . 5 6	1 . 0	6 8	5 9	5 3	4 9	6 7	5 9	5 3	4 9	6 4	5 7	5 2	4 8	6 2	5 6	5 2	4 8	4 6
				1 . 2 5	7 3	6 6	6 0	5 6	7 2	6 5	6 0	5 5	6 9	6 3	5 9	5 5	6 7	6 2	5 8	5 5	5 3
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 7	7 0	6 5	6 0	7 5	6 9	6 4	6 0	7 3	6 8	6 3	6 0	7 1	6 6	6 2	5 9	5 7	
			2 . 0	8 1	7 6	7 1	6 8	8 0	7 5	7 1	6 7	7 8	7 3	7 0	6 6	7 5	7 2	6 8	6 6	6 4	
			2 . 5	8 4	7 9	7 6	7 2	8 3	7 9	7 5	7 2	8 0	7 7	7 4	7 1	7 8	7 5	7 2	7 0	6 8	
			3 . 0	8 6	8 2	7 9	7 6	8 5	8 1	7 8	7 5	8 2	7 9	7 6	7 4	8 0	7 8	7 5	7 3	7 1	
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	8 8	8 5	8 2	8 0	8 7	8 4	8 2	7 9	8 5	8 2	8 0	7 8	8 3	8 1	7 9	7 7	7 5	
			5 . 0	9 0	8 7	8 5	8 3	8 9	8 6	8 4	8 2	8 6	8 4	8 2	8 1	8 4	8 3	8 1	8 0	7 7	
			7 . 0	9 1	8 9	8 8	8 6	9 0	8 8	8 7	8 5	8 8	8 7	8 5	8 4	8 6	8 5	8 4	8 2	8 0	
			1 0 . 0	9 3	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 9	8 8	8 7	8 6	8 7	8 6	8 6	8 5	8 2	

