

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 1 K
光源	L L D 4 0 0 0 L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 5 4 7 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	39	32	27	24	38	31	27	24	37	31	27	24	35	30	26	24	23
			0 . 6 3	0 . 8	46	39	35	31	45	39	34	31	43	38	34	31	42	37	34	31	30
			0 . 5 6	1 . 0	50	44	40	37	49	44	40	36	47	43	39	36	46	42	39	36	35
				1 . 2 5	54	48	45	41	53	48	44	41	51	47	44	41	49	46	43	41	39
下方投影面積		c m ²		1 . 5	56	51	48	45	55	51	47	45	53	50	47	44	52	49	46	44	43
			等価発光面積	c m ²	2 . 0	59	56	52	50	58	55	52	50	57	54	51	49	55	53	50	49
取付 高さ	器具間隔最大限			2 . 5	61	58	55	53	60	57	55	53	59	56	54	52	57	55	53	51	50
	横方向 (A) 縦方向 (B)			3 . 0	63	60	57	55	62	59	57	55	60	58	56	54	58	57	55	54	52
H m	1 . 2 5 H m	1 . 2 5 H m		4 . 0	64	62	60	58	63	61	60	58	62	60	58	57	60	59	57	56	55
				5 . 0	65	63	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56
				7 . 0	66	65	64	63	65	64	63	62	64	63	62	61	62	62	61	60	58
				10 . 0	67	66	65	64	66	65	65	64	65	64	63	63	63	63	62	62	60

