

屋内照明器具特性

品番 (品名)	LGB16124															
光源	LLD3000CU1 x1 795.0 lm															
管理番号	K0179044(0)DR1															
BZ分類	BZ5/0.9/BZ4															

器具効率	92%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	92%		室指数	照明率 (X0.01) ZCM																
保守率	良 0.67 中 0.63 否 0.56	0.6	53	42	34	29	51	41	34	29	49	40	34	29	47	39	33	29	27	
		0.8	62	52	45	40	61	51	44	39	58	50	44	39	56	49	43	39	37	
		1.0	68	59	52	47	67	58	52	47	64	57	51	46	62	55	50	46	44	
		1.25	74	66	59	54	73	65	59	54	70	63	58	53	67	62	57	53	51	
下方投影面積	c m ²	1.5	78	70	64	60	77	69	64	59	74	68	63	59	71	66	62	58	56	
		2.0	83	77	72	68	82	76	71	67	79	74	70	66	77	72	69	66	64	
取付高さ	器具間隔最大限		2.5	86	81	77	73	85	80	76	72	82	78	75	72	80	76	73	71	68
	横方向 (A)	縦方向 (B)	3.0	89	84	80	77	87	83	79	76	85	81	78	75	82	79	77	74	72
H m	1.29 H m	1.29 H m	4.0	91	88	85	82	90	87	84	81	88	85	82	80	85	83	81	79	76
			5.0	93	90	87	85	92	89	87	84	89	87	85	83	87	85	83	82	79
			7.0	95	93	91	89	94	92	90	88	91	90	88	87	89	88	86	85	83
			10.0	96	95	93	92	95	94	92	91	93	92	90	89	91	90	89	88	85

