

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 2 K
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 8 9 4 2 (0) D R 1
B Z 分類	B Z 3 / 6 . 0 / B Z 4

器具効率		7 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 8	4 0	3 4	3 1	4 7	3 9	3 4	3 1	4 5	3 8	3 4	3 1	4 4	3 8	3 4	3 0	2 9
			0 . 6 3	0 . 8	5 5	4 8	4 3	3 9	5 4	4 7	4 2	3 9	5 2	4 6	4 2	3 9	5 1	4 5	4 1	3 8	3 7
			0 . 5 6	1 . 0	6 0	5 3	4 8	4 5	5 9	5 3	4 8	4 5	5 7	5 1	4 7	4 4	5 5	5 0	4 7	4 4	4 2
				1 . 2 5	6 4	5 8	5 3	5 0	6 3	5 7	5 3	5 0	6 1	5 6	5 2	4 9	5 9	5 5	5 2	4 9	4 7
下方投影面積		c m ²	1 . 5	6 7	6 1	5 7	5 4	6 6	6 1	5 7	5 3	6 3	5 9	5 6	5 3	6 2	5 8	5 5	5 2	5 1	
			2 . 0	7 0	6 6	6 2	5 9	6 9	6 5	6 2	5 9	6 7	6 3	6 1	5 8	6 5	6 2	6 0	5 7	5 6	
等価発光面積		c m ²	2 . 5	7 2	6 9	6 5	6 3	7 1	6 8	6 5	6 2	6 9	6 6	6 4	6 1	6 7	6 5	6 3	6 1	5 9	
			3 . 0	7 4	7 0	6 8	6 5	7 3	7 0	6 7	6 5	7 1	6 8	6 6	6 4	6 9	6 7	6 5	6 3	6 1	
H m	1 . 1 7 H m	1 . 1 7 H m	4 . 0	7 6	7 3	7 1	6 9	7 5	7 2	7 0	6 8	7 3	7 1	6 9	6 7	7 1	6 9	6 7	6 6	6 4	
			5 . 0	7 7	7 5	7 3	7 1	7 6	7 4	7 2	7 0	7 4	7 2	7 1	6 9	7 2	7 1	6 9	6 8	6 6	
			7 . 0	7 8	7 6	7 5	7 4	7 7	7 6	7 4	7 3	7 5	7 4	7 3	7 2	7 3	7 2	7 1	7 0	6 8	
			1 0 . 0	7 9	7 8	7 7	7 6	7 8	7 7	7 6	7 5	7 6	7 5	7 4	7 4	7 4	7 4	7 3	7 2	7 0	

