

# 屋内照明器具特性

品番 (品名)	LGB16125									
光源	LLD4000LCB1 ×1					845.0 1 m				
管理番号	K0176300(0)DR1									
BZ分類	BZ2									

器具効率	47%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		47%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	31	26	23	21	31	26	23	21	30	26	23	21	29	25	23	21	20	
	中	0.63	0.8	36	32	29	27	35	32	29	27	34	31	29	27	33	30	28	27	26	
	否	0.56	1.0	39	35	33	31	38	35	32	31	37	34	32	30	36	34	32	30	29	
			1.25	41	38	36	34	41	38	35	34	40	37	35	33	39	36	35	33	32	
下方投影面積			c m <sup>2</sup>	1.5	43	40	38	36	42	40	37	36	41	39	37	36	40	38	37	35	34
	等価発光面積		c m <sup>2</sup>	2.0	45	42	41	39	44	42	40	39	43	41	40	38	42	40	39	38	37
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	1.28 H m	1.28 H m	2.5	46	44	42	41	45	43	42	41	44	43	41	40	43	42	41	40	39	
			3.0	47	45	44	42	46	44	43	42	45	44	42	41	44	43	42	41	40	
			4.0	48	46	45	44	47	46	45	44	46	45	44	43	45	44	43	43	41	
			5.0	48	47	46	45	48	47	46	45	46	46	45	44	45	45	44	44	42	
			7.0	49	48	47	47	48	48	47	46	47	47	46	45	46	46	45	45	43	
			10.0	49	49	48	48	49	48	48	47	48	47	47	46	47	46	46	46	44	

