

屋内照明器具特性

品番 (品名) **LGB16125**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176305(0)DR1**

BZ分類 **BZ1**

器具効率	77%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	77%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	65	61	58	56	65	60	58	56	64	60	58	56	63	60	57	56	55
	中	0.63	0.8	70	66	63	61	69	65	63	61	68	65	63	61	67	64	62	61	60
	否	0.56	1.0	72	69	66	65	72	69	66	64	71	68	66	64	69	67	65	64	63
下方投影面積	等価発光面積	cm ²	1.25	75	72	69	67	74	71	69	67	73	70	68	67	71	69	68	66	65
			1.5	76	73	71	70	75	73	71	69	74	72	70	69	73	71	69	68	67
取付高さ	器具間隔最大限		2.5	79	77	75	74	78	76	75	74	77	75	74	73	75	74	73	72	71
	横方向 (A)	縦方向 (B)	3.0	80	78	77	75	79	77	76	75	77	76	75	74	76	75	74	73	72
H _m	0.40H _m	0.40H _m	4.0	80	79	78	77	80	78	77	77	78	77	76	75	77	76	75	74	73
			5.0	81	80	79	78	80	79	78	78	78	78	77	76	77	76	76	75	73
			7.0	82	81	80	79	81	80	79	79	79	78	78	77	77	77	77	76	74
			10.0	82	81	81	80	81	81	80	80	79	79	79	78	78	78	77	77	75

