

# 屋内照明器具特性

品番 (品名)	LGB16125									
光源	LLD40001CQ1 ×1					845.0 lm				
管理番号	K0176302(0)DR1									
BZ分類	BZ2									

器具効率	56%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 ( X0.01 )																		ZCM																	
下方光束	56%																																																						
保守率	良 中 否	0.67	0.6	3.7	3.1	2.8	2.6	3.6	3.1	2.8	2.5	3.5	3.1	2.8	2.5	3.4	3.0	2.7	2.5	2.4																																			
		0.63	0.8	4.3	3.8	3.5	3.2	4.2	3.8	3.4	3.2	4.1	3.7	3.4	3.2	4.0	3.6	3.4	3.2	3.1																																			
		0.56	1.0	4.6	4.2	3.9	3.7	4.6	4.2	3.9	3.6	4.4	4.1	3.8	3.6	4.3	4.0	3.8	3.6	3.5																																			
			1.25	4.9	4.5	4.3	4.0	4.8	4.5	4.2	4.0	4.7	4.4	4.2	4.0	4.6	4.3	4.1	4.0	3.9																																			
下方投影面積		cm <sup>2</sup>																																																					
等価発光面積		cm <sup>2</sup>																																																					
取付高さ	器具間隔最大限																																																						
	横方向 (A)	縦方向 (B)																																																					
Hm	1.28Hm	1.28Hm	4.0	5.7	5.5	5.4	5.3	5.6	5.5	5.3	5.2	5.5	5.3	5.2	5.1	5.3	5.2	5.1	4.9																																				
			5.0	5.7	5.6	5.5	5.4	5.7	5.6	5.4	5.4	5.5	5.4	5.3	5.3	5.4	5.3	5.3	5.2																																				
			7.0	5.8	5.7	5.6	5.6	5.7	5.7	5.6	5.5	5.6	5.5	5.5	5.4	5.5	5.4	5.4	5.3																																				
			10.0	5.9	5.8	5.7	5.7	5.8	5.7	5.7	5.6	5.7	5.6	5.6	5.5	5.5	5.5	5.4	5.3																																				

