

屋内照明器具特性	
品番 (品名)	NTN88081B
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0179220 (0) DR 1
BZ分類	BZ5

器具効率		97 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.69	0.6	53	42	34	29	52	41	33	28	49	39	33	28	46	38	32	27	25				
			0.67	0.8	63	52	44	38	61	51	43	38	58	49	42	37	55	47	41	37	34				
			0.63	1.0	69	59	51	45	67	58	50	45	64	55	49	44	60	53	48	43	40				
				1.25	75	65	58	53	73	64	57	52	69	62	56	51	65	59	54	50	47				
下方投影面積		cm ²		1.5	79	70	63	58	77	69	62	57	73	66	61	56	69	63	59	55	51				
			等価発光面積	cm ²	2.0	85	77	71	66	82	76	70	65	78	73	68	64	75	70	66	62	58			
取付高さ	器具間隔最大限			2.5	88	82	76	72	86	80	75	71	82	77	73	69	78	74	70	67	63				
	横方向 (A) 縦方向 (B)			3.0	90	85	80	76	88	83	79	75	84	80	76	73	80	77	74	71	67				
H m	1.27 H m	1.27 H m		4.0	94	89	85	81	91	87	84	80	87	84	81	78	84	81	78	76	72				
				5.0	95	92	88	85	93	90	87	84	89	87	84	81	86	83	81	79	75				
				7.0	98	95	92	90	96	93	91	88	92	90	88	86	88	86	85	83	79				
				10.0	99	97	95	93	97	95	94	92	94	92	90	89	90	89	87	86	82				

