

屋内照明器具特性

品番 (品名) **LGB10829**

光源 **LLD2020LCE1 x1** **460.0lm**

管理番号 **K0176307(0)DR1**

BZ分類 **BZ1**

器具効率	87%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	87%	床		10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	74	69	66	63	73	69	66	63	72	68	65	63	71	68	65	63	62	
	中 0.63	0.8	79	75	72	69	78	74	71	69	77	74	71	69	76	73	71	69	68	
	否 0.56	1.0	82	78	75	73	81	78	75	73	80	77	75	73	79	76	74	72	71	
下方投影面積 等価発光面積	cm ²	1.25	85	81	79	77	84	81	78	76	82	80	78	76	81	79	77	75	74	
		1.5	86	83	81	79	85	83	80	79	84	81	80	78	82	80	79	77	76	
取付高さ	器具間隔最大限		2.0	88	86	84	82	87	85	83	82	86	84	82	81	84	83	81	80	79
	横方向 (A)	縦方向 (B)	2.5	89	87	86	84	89	87	85	84	87	85	84	83	85	84	83	82	80
Hm	0.40Hm	0.40Hm	3.0	90	88	87	85	89	88	86	85	88	86	85	84	86	85	84	83	81
			4.0	91	90	89	87	90	89	88	87	88	87	86	86	87	86	85	84	83
			5.0	92	91	90	89	91	90	89	88	89	88	87	87	87	87	86	85	83
			7.0	92	92	91	90	91	91	90	89	90	89	88	88	88	87	87	86	84
			10.0	93	92	92	91	92	91	91	90	90	90	89	89	88	88	87	85	

