

# 屋内照明器具特性

品番 (品名)	LGB15118				
光源	LLD4000LCT1 ×1                      845.0 1 m				
管理番号	K0190516 ( 0 ) DR 1				
BZ分類	BZ3				

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	0 %	室指数																			照明率 ( X0.01 )																			ZCM																		
下方光束	67 %																																																									
保守率	良 中 否	0.67	0.6	4.4	3.7	3.3	3.0	4.4	3.7	3.3	3.0	4.2	3.6	3.3	3.0	4.1	3.6	3.2	3.0	2.9																																						
		0.63	0.8	5.0	4.4	3.9	3.6	4.9	4.3	3.9	3.6	4.8	4.3	3.9	3.6	4.6	4.2	3.8	3.6	3.5																																						
		0.56	1.0	5.4	4.8	4.4	4.1	5.3	4.8	4.4	4.0	5.1	4.7	4.3	4.0	5.0	4.6	4.3	4.0	3.9																																						
			1.25	5.7	5.2	4.8	4.5	5.6	5.1	4.8	4.5	5.5	5.0	4.7	4.4	5.3	4.9	4.6	4.4	4.3																																						
下方投影面積	c m <sup>2</sup>	1.5	6.0	5.5	5.1	4.8	5.9	5.4	5.1	4.8	5.7	5.3	5.0	4.7	5.5	5.2	4.9	4.7	4.6																																							
		2.0	6.3	5.9	5.5	5.3	6.2	5.8	5.5	5.2	6.0	5.7	5.4	5.2	5.8	5.6	5.3	5.1	5.0																																							
取付高さ	器具間隔最大限		2.5	6.5	6.1	5.8	5.6	6.4	6.1	5.8	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.3																																						
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.0	5.8	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.6	5.5																																						
H m	1.32 H m	1.32 H m	4.0	6.8	6.5	6.3	6.1	6.7	6.5	6.3	6.1	6.5	6.3	6.1	6.0	6.3	6.2	6.0	5.9	5.7																																						
			5.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.4	6.3	6.2	6.1	5.9																																						
			7.0	7.0	6.8	6.7	6.6	6.9	6.8	6.6	6.5	6.7	6.6	6.5	6.4	6.6	6.5	6.4	6.3	6.1																																						
			10.0	7.1	7.0	6.9	6.8	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.7	6.6	6.5	6.5	6.3																																						

