

屋内照明器具特性	
品番 (品名)	LGB10829
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0179039(0)DR1
BZ分類	BZ2/8.5/BZ1

器具効率	59%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	59%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.9	3.3	3.0	2.7	3.9	3.3	3.0	2.7	3.8	3.3	2.9	2.7	3.6	3.2	2.9	2.7	2.6
	中	0.63	0.8	4.6	4.1	3.7	3.4	4.5	4.0	3.7	3.4	4.4	3.9	3.6	3.4	4.2	3.9	3.6	3.4	3.3
	否	0.56	1.0	5.0	4.5	4.2	3.9	4.9	4.5	4.2	3.9	4.7	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8
			1.25	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.9	4.7	4.4	4.3	4.2
下方投影面積			1.5	5.4	5.1	4.8	4.6	5.4	5.1	4.8	4.6	5.2	5.0	4.7	4.6	5.1	4.9	4.7	4.5	4.4
			2.0	5.7	5.4	5.2	5.0	5.6	5.4	5.2	5.0	5.5	5.3	5.1	4.9	5.3	5.2	5.0	4.9	4.8
取付高さ	器具間隔最大限		2.5	5.8	5.6	5.4	5.2	5.8	5.5	5.4	5.2	5.6	5.4	5.3	5.2	5.5	5.3	5.2	5.1	5.0
	横方向 (A)	縦方向 (B)	3.0	5.9	5.7	5.6	5.4	5.9	5.7	5.5	5.4	5.7	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.1
Hm	1.28Hm	1.28Hm	4.0	6.0	5.9	5.8	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.3
			5.0	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.8	5.7	5.6	5.6	5.4
			7.0	6.2	6.1	6.0	5.9	6.1	6.0	6.0	5.9	6.0	5.9	5.8	5.8	5.9	5.8	5.7	5.7	5.5
			10.0	6.3	6.2	6.1	6.1	6.2	6.1	6.1	6.0	6.0	6.0	5.9	5.9	5.9	5.9	5.8	5.8	5.6

