

屋内照明器具特性

品番 (品名)	LGB10829									
光源	LLD2000CU1 x1					566.0 lm				
管理番号	K0179040(0)DR1									
BZ分類	BZ2/8.5/BZ1									

器具効率	62%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	62%																																																						
保守率	良 中 否	0.67	0.6	41	35	31	28	40	35	31	28	39	34	31	28	38	34	30	28	27																																			
		0.63	0.8	48	42	39	36	47	42	39	36	46	41	38	36	44	41	38	36	35																																			
		0.56	1.0	52	47	44	41	51	47	43	41	50	46	43	41	48	45	43	41	40																																			
			1.25	55	51	48	45	54	50	48	45	53	50	47	45	51	49	46	45	44																																			
下方投影面積	c m ²	1.5	57	53	51	48	56	53	50	48	55	52	50	48	53	51	49	47	46																																				
		2.0	60	57	54	52	59	56	54	52	57	55	53	52	56	54	52	51	50																																				
取付高さ	器具間隔最大限		2.5	61	59	57	55	60	58	56	55	59	57	55	54	57	56	55	53	52																																			
	横方向 (A)	縦方向 (B)	3.0	62	60	58	57	61	59	58	56	60	58	57	56	58	57	56	55	53																																			
H m	1.28 H m	1.28 H m	4.0	63	62	60	59	63	61	60	59	61	60	59	58	60	59	58	57	55																																			
			5.0	64	63	62	60	63	62	61	60	62	61	60	59	60	60	59	58	57																																			
			7.0	65	64	63	62	64	63	62	62	63	62	61	61	61	61	60	60	58																																			
			10.0	65	65	64	63	65	64	63	63	63	63	62	62	62	61	61	61	59																																			

