

屋内照明器具特性

品番 (品名) **LGB10829**

光源 **LLD2020CU1 ×1** **468.0 lm**

管理番号 **K0179043(0)DR1**

BZ分類 **BZ1**

器具効率	85%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	85%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	74	69	66	64	73	69	66	64	72	68	66	64	71	68	66	64	63
	中	0.63	0.8	79	74	72	70	78	74	71	69	77	73	71	69	76	73	71	69	68
	否	0.56	1.0	81	78	75	73	81	77	75	73	79	76	74	73	78	76	74	72	71
下方投影面積 等価発光面積	cm ²	cm ²	1.25	84	80	78	76	83	80	78	76	81	79	77	75	80	78	76	75	74
			1.5	85	82	80	78	84	82	80	78	83	81	79	77	81	80	78	77	76
			2.0	87	85	83	81	86	84	82	81	85	83	81	80	83	82	80	79	78
取付高さ	器具間隔最大限		2.5	88	86	84	83	87	85	84	83	86	84	83	82	84	83	82	81	79
	横方向 (A)	縦方向 (B)	3.0	89	87	86	84	88	86	85	84	86	85	84	83	85	84	83	82	80
Hm	0.34Hm	0.34Hm	4.0	90	88	87	86	89	88	87	86	87	86	85	84	85	85	84	83	81
			5.0	90	89	88	87	89	88	88	87	88	87	86	85	86	85	85	85	84
			7.0	91	90	89	89	90	89	89	88	88	88	87	87	86	86	86	85	83
			10.0	91	91	90	90	90	90	89	89	89	88	88	87	87	87	86	86	84

