

屋内照明器具特性

品番 (品名)	LGB16748				
光源	LLD4000MLCE1 ×1		845.0 l m		
管理番号	K0176320(0)DR1				
BZ分類	BZ3				

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	0 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	63 %																																																			
保守率	良 中 否	0.67	0.6	41	35	31	28	40	34	31	28	39	34	30	28	38	33	30	28	27																																
		0.63	0.8	47	41	37	34	46	40	36	34	44	39	36	33	43	39	36	33	32																																
		0.56	1.0	50	45	41	38	49	44	40	38	48	43	40	37	46	42	39	37	36																																
			1.25	53	48	45	42	52	48	44	42	51	47	44	41	49	46	43	41	40																																
下方投影面積	c m ²	1.5	55	51	47	45	54	50	47	44	53	49	46	44	51	48	46	44	42																																	
		2.0	58	55	51	49	57	54	51	49	56	53	50	48	54	52	49	48	46																																	
取付高さ	器具間隔最大限		2.5	60	57	54	52	59	56	54	52	57	55	53	51	56	54	52	50	49																																
	横方向 (A)	縦方向 (B)	3.0	61	59	56	54	60	58	56	54	59	57	55	53	57	55	54	52	51																																
H m	1.32 H m	1.32 H m	4.0	63	61	59	57	62	60	58	57	60	59	57	56	59	57	56	55	53																																
			5.0	64	62	60	59	63	61	60	58	61	60	59	57	60	59	58	57	55	55																															
			7.0	65	64	62	61	64	63	62	61	63	61	61	60	61	60	59	59	57																																
			10.0	66	65	64	63	65	64	63	62	63	63	62	61	62	61	61	60	58																																

