

# 屋内照明器具特性

品番 (品名) **LGB16129**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176305(0)DR1**

BZ分類 **BZ1**

器具効率	77%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	77%	床		10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	65	61	58	56	65	60	58	56	64	60	58	56	63	60	57	56	55	
	中 0.63	0.8	70	66	63	61	69	65	63	61	68	65	63	61	67	64	62	61	60	
	否 0.56	1.0	72	69	66	65	72	69	66	64	71	68	66	64	69	67	65	64	63	
下方投影面積	cm <sup>2</sup>	1.25	75	72	69	67	74	71	69	67	73	70	68	67	71	69	68	66	65	
		1.5	76	73	71	70	75	73	71	69	74	72	70	69	73	71	69	68	67	
等価発光面積	cm <sup>2</sup>	2.0	78	76	74	72	77	75	73	72	76	74	73	71	74	73	72	71	69	
		2.5	79	77	75	74	78	76	75	74	77	75	74	73	75	74	73	72	71	
取付高さ	器具間隔最大限		3.0	80	78	77	75	79	77	76	75	77	76	75	74	76	75	74	73	72
	横方向 (A)	縦方向 (B)	4.0	80	79	78	77	80	78	77	77	78	77	76	75	77	76	75	74	73
Hm	0.40Hm	0.40Hm	5.0	81	80	79	78	80	79	78	78	78	77	76	77	76	76	75	73	
			7.0	82	81	80	79	81	80	79	79	79	78	78	77	77	77	76	74	
			10.0	82	81	81	80	81	81	80	80	79	79	79	78	78	77	77	75	

