

屋内照明器具特性

品番 (品名)	NNF J 4 2 8 4 8																			
光源	LDL40S . N / 29 / 31 - 9 (3150 A) × 2										3150.0 1 m									
管理番号	K0127197 (5) DB 1																			
B Z 分類	BZ6 / 4.5 / BZ5 / 6.0 / BZ6																			

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	88 %		室指数	照明率 (X0.01)																			
保守率	良	0.93	0.6	4.9	3.7	3.0	2.4	4.8	3.7	2.9	2.4	4.5	3.5	2.9	2.4	4.2	3.4	2.8	2.3	2.1			
	中	0.9	0.8	5.8	4.7	3.9	3.3	5.6	4.6	3.8	3.3	5.3	4.4	3.7	3.2	5.0	4.2	3.6	3.2	2.9			
	否	0.86	1.0	6.4	5.3	4.6	4.0	6.2	5.2	4.5	3.9	5.9	5.0	4.3	3.8	5.5	4.8	4.2	3.8	3.5			
			1.25	7.0	6.0	5.2	4.6	6.8	5.8	5.1	4.6	6.4	5.6	5.0	4.5	6.0	5.4	4.8	4.4	4.1			
下方投影面積			1.5	7.4	6.4	5.7	5.1	7.2	6.3	5.6	5.1	6.8	6.0	5.4	5.0	6.4	5.8	5.3	4.9	4.5			
等価発光面積			2.0	7.9	7.1	6.5	5.9	7.7	7.0	6.4	5.9	7.3	6.7	6.2	5.7	6.9	6.4	6.0	5.6	5.2			
取付高さ	器具間隔最大限		2.5	8.3	7.6	7.0	6.5	8.1	7.4	6.9	6.4	7.6	7.1	6.6	6.2	7.3	6.8	6.4	6.1	5.7			
	横方向 (A)	縦方向 (B)	3.0	8.5	7.9	7.4	6.9	8.3	7.7	7.3	6.8	7.9	7.4	7.0	6.6	7.5	7.1	6.8	6.5	6.1			
1.5m	2.14 m	2.11 m	4.0	8.8	8.3	7.9	7.5	8.6	8.2	7.8	7.4	8.2	7.9	7.5	7.2	7.9	7.5	7.3	7.0	6.6			
2	2.83	2.68	5.0	9.0	8.6	8.2	7.9	8.8	8.5	8.1	7.8	8.5	8.1	7.8	7.6	8.1	7.8	7.6	7.3	6.9			
2.5	3.52	3.25	7.0	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.7	8.5	8.2	8.0	8.3	8.1	7.9	7.8	7.3			
3	4.19	3.84	10.0	9.5	9.2	9.0	8.8	9.3	9.1	8.9	8.7	8.9	8.7	8.6	8.4	8.6	8.4	8.3	8.1	7.7			

