

屋内照明器具特性

品番 (品名)	NYY41013	
光源	LED3000_70_1510 x1 1510.0lm	
管理番号	K0171208(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 51%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	50%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.69	0.6	63	54	49	45	59	52	47	44	53	47	43	41	47	43	40	38	33	
	中 0.67		70	62	57	53	66	59	55	51	58	53	50	47	51	48	45	43	37	
	否 0.63		1.0	75	68	63	59	70	64	60	56	62	57	54	52	54	51	49	47	40
下方投影面積	cm ²	1.25	79	73	68	64	74	69	65	61	65	61	58	56	56	54	52	50	42	
		1.5	82	76	72	68	77	72	68	65	67	64	61	59	58	56	54	52	43	
等価発光面積	cm ²	2.0	86	81	77	74	80	76	73	70	70	67	65	63	60	58	57	55	45	
		2.5	88	84	81	78	83	79	76	74	72	69	67	65	62	60	59	57	46	
取付高さ	器具間隔最大限		3.0	90	86	83	81	84	81	78	76	73	71	69	67	62	61	60	59	46
	横方向 (A)	縦方向 (B)	4.0	92	89	87	84	86	84	81	80	74	73	71	70	64	63	62	61	47
Hm	0.24Hm	0.24Hm	5.0	93	91	89	87	87	85	83	82	75	74	73	72	64	64	63	62	48
			7.0	95	93	91	90	88	87	86	84	77	76	75	74	65	65	64	63	48
			10.0	96	95	93	92	89	88	87	86	77	77	76	75	66	65	65	64	49

