

屋内照明器具特性	
品番 (品名)	NNFL41271
光源	LED4000_85_3070 x1 3070.0 lm
管理番号	K0197867(0)D 1
BZ分類	BZ6/1.1/BZ5/1.8/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	14%	床	10%				10%				10%				10%				0%	
下方光束	86%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.83 中 0.81 否 0.77	0.6	52	40	32	26	50	39	31	26	46	36	30	25	43	34	28	24	21	
		0.8	62	50	41	35	59	48	40	35	55	45	39	34	51	43	37	32	29	
		1.0	68	57	48	42	65	55	47	41	61	52	45	40	56	49	43	38	34	
		1.25	74	63	55	49	71	61	54	48	66	58	51	46	61	54	49	45	40	
下方投影面積	c m ²	1.5	78	68	61	55	75	66	59	54	70	62	56	51	65	59	53	49	45	
		2.0	84	75	68	63	81	73	67	61	75	69	63	59	70	65	60	56	51	
取付高さ	器具間隔最大限		2.5	87	80	74	69	84	78	72	67	79	73	68	64	73	69	65	61	56
	横方向 (A)	縦方向 (B)	3.0	90	83	78	73	87	81	76	71	81	76	72	68	76	72	68	65	59
1.5m	2.09m	2.08m	4.0	93	88	83	79	90	85	81	77	85	81	77	74	79	76	73	70	64
2	2.75	2.61	5.0	95	91	87	83	92	88	85	81	87	83	80	77	81	79	76	74	68
2.5	3.42	3.17	7.0	98	94	91	88	95	92	89	86	89	87	84	82	84	82	80	78	72
3	4.08	3.74	10.0	100	97	95	92	97	95	92	90	91	89	88	86	86	85	83	82	75

