

屋内照明器具特性	
品番 (品名)	NNFL41510
光源	LED5000_85_4000 x1 4000.0 lm
管理番号	K0172825(0)DR1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	20%	床	10%				10%				10%				10%				0%	
下方光束	80%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19
	中	0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26
	否	0.77	1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31
			1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37
下方投影面積		cm <sup>2</sup>	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41
等価発光面積		cm <sup>2</sup>	2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47
取付高さ	器具間隔最大限		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55
1.5m	2.26m	2.24m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59
2	2.95	2.74	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62
2.5	3.66	3.29	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66
3	4.37	3.85	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69

