

# 屋内照明器具特性

|         |                   |  |  |  |  |          |  |  |  |  |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | LRDC1144N         |  |  |  |  |          |  |  |  |  |
| 光源      | LED5000_70_340 x1 |  |  |  |  | 340.0 lm |  |  |  |  |
| 管理番号    | K0157035(0)D 1    |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ3/1.1/BZ2       |  |  |  |  |          |  |  |  |  |

|        |               |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |    |     |
|--------|---------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|-----|
| 器具効率   | 100%          | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |     | 0% |    |     |
|        | 上方光束          |         | 0%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束          |         | 100% |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |    | ZCM |
| 保守率    | 良             | 0.67    | 0.6  | 64  | 53  | 47  | 42  | 63  | 53  | 46  | 42  | 61  | 52  | 46  | 42  | 59  | 51 | 46  | 42 | 40 |     |
|        | 中             | 0.63    | 0.8  | 75  | 65  | 59  | 54  | 73  | 64  | 58  | 54  | 71  | 63  | 58  | 54  | 69  | 62 | 57  | 53 | 52 |     |
|        | 否             | 0.56    | 1.0  | 81  | 73  | 67  | 62  | 80  | 72  | 66  | 62  | 78  | 71  | 66  | 62  | 75  | 69 | 65  | 61 | 59 |     |
|        |               |         | 1.25 | 87  | 79  | 74  | 70  | 86  | 79  | 74  | 69  | 83  | 77  | 73  | 69  | 81  | 76 | 72  | 68 | 67 |     |
| 下方投影面積 |               |         | 1.5  | 90  | 84  | 79  | 75  | 89  | 83  | 78  | 75  | 87  | 81  | 77  | 74  | 84  | 80 | 76  | 73 | 71 |     |
|        | 等価発光面積        |         | 2.0  | 95  | 90  | 86  | 82  | 94  | 89  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 85 | 83  | 80 | 78 |     |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 98  | 93  | 90  | 87  | 97  | 92  | 89  | 86  | 94  | 91  | 88  | 85  | 92  | 89 | 86  | 84 | 82 |     |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 100 | 96  | 93  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 90  | 88  | 94  | 91 | 89  | 87 | 85 |     |
| Hm     | 1.16Hm        | 1.20Hm  | 4.0  | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 93  | 98  | 96  | 94  | 92  | 96  | 94 | 92  | 91 | 88 |     |
|        |               |         | 5.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 94  | 97  | 96 | 94  | 93 | 91 |     |
|        |               |         | 7.0  | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98 | 97  | 96 | 93 |     |
|        |               |         | 10.0 | 106 | 105 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 100 | 99 | 98  | 98 | 95 |     |

