

屋内照明器具特性	
品番 (品名)	L G W5 1 7 6 9 B
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0181593 (0) DR 1
B Z 分類	BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	44	34	27	23	42	33	27	22	39	31	25	21	36	29	24	21	18
			0.6	0.8	52	42	35	31	50	41	35	30	46	39	33	29	43	36	32	28	25
			0.56	1.0	57	48	41	36	55	47	40	36	51	44	39	34	47	41	37	33	30
				1.25	62	54	47	42	60	52	46	42	55	49	44	40	51	46	42	38	35
下方投影面積 等価発光面積		c m ²		1.5	65	58	52	47	63	56	50	46	59	53	48	44	55	50	46	42	38
				2.0	70	64	58	54	68	62	57	53	63	58	54	50	59	55	51	48	44
				2.5	73	67	63	59	71	65	61	57	66	62	58	55	62	58	55	52	48
				3.0	75	70	66	62	73	68	64	61	68	64	61	58	64	61	58	55	51
H m	1.31 H m	1.31 H m		4.0	78	74	70	67	75	72	68	66	71	68	65	63	66	64	62	60	55
				5.0	80	76	73	70	77	74	71	69	72	70	68	65	68	66	64	62	57
				7.0	81	79	77	74	79	77	75	73	74	73	71	69	70	69	67	66	60
				10.0	83	81	79	78	81	79	77	76	76	75	73	72	72	71	69	68	63

