

屋内照明器具特性	
品番 (品名)	L G W5 1 7 7 9 B
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0182053 (0) DR 1
B Z 分類	BZ5 / 0.9 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		56 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.63	0.6	32	25	21	18	31	25	21	18	30	24	21	18	29	24	20	18	17
			0.6	0.8	38	31	27	24	37	31	27	24	35	30	26	24	34	29	26	23	22
			0.56	1.0	41	35	31	28	40	35	31	28	39	34	30	28	37	33	30	28	26
				1.25	44	39	35	32	44	39	35	32	42	38	34	32	40	37	34	32	30
下方投影面積		c m ²		1.5	47	42	38	35	46	41	38	35	44	40	37	35	43	39	37	34	33
			等価発光面積	c m ²	2.0	50	46	43	40	49	45	42	40	47	44	41	39	46	43	41	39
取付 高さ	器具間隔最大限			2.5	52	48	45	43	51	48	45	43	49	47	44	42	48	45	43	42	40
	横方向 (A)		縦方向 (B)	3.0	53	50	48	45	52	50	47	45	51	48	46	44	49	47	45	44	42
H m	1.22 H m	1.22 H m		4.0	55	52	50	49	54	52	50	48	52	51	49	47	51	49	48	47	45
				5.0	56	54	52	51	55	53	52	50	54	52	51	49	52	51	50	49	47
				7.0	57	56	54	53	56	55	54	53	55	54	53	52	53	52	52	51	49
				10.0	58	57	56	55	57	56	55	54	56	55	54	53	54	54	53	53	51

