

# 屋内照明器具特性

品番 (品名)	S P L 5 4 2 7	
光源	LLD2000LCE1 ×4	531.0 lm
管理番号	K0176039 (0) DR 1	
BZ分類	BZ5	

器具効率	85%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	85%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	48	38	31	27	47	38	31	27	45	37	31	27	43	36	30	27	25
	中	0.63	0.8	57	47	41	36	56	47	40	36	53	45	40	35	51	44	39	35	33
	否	0.56	1.0	63	54	47	42	61	53	47	42	59	52	46	42	57	50	45	41	40
			1.25	68	60	53	49	66	59	53	48	64	57	52	48	61	56	51	48	46
下方投影面積	cm <sup>2</sup>		1.5	71	64	58	53	70	63	58	53	67	61	57	53	65	60	56	52	50
	等価発光面積		cm <sup>2</sup>	2.0	76	70	65	61	75	69	64	60	72	67	63	60	70	66	62	59
取付高さ	器具間隔最大限		2.5	79	74	69	65	78	73	69	65	75	71	67	64	73	69	66	63	61
	横方向 (A)	縦方向 (B)	3.0	81	77	73	69	80	76	72	69	77	74	71	68	75	72	69	67	65
Hm	1.27Hm	1.27Hm	4.0	84	80	77	74	82	79	76	73	80	77	75	72	78	75	73	71	69
			5.0	85	82	80	77	84	81	79	77	82	79	77	75	80	78	76	74	72
			7.0	87	85	83	81	86	84	82	80	84	82	80	79	82	80	79	78	75
			10.0	89	87	86	84	87	86	85	83	85	84	83	82	83	82	81	80	78

