

# 屋内照明器具特性

品番 (品名)	S P L 5 4 2 8	
光源	LLD2000LCE1 ×4	531.0 lm
管理番号	K0176043 (0) DR 1	
BZ分類	BZ5	

器具効率	84%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	84%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	48	37	31	26	47	37	31	26	45	36	30	26	43	35	30	26	25
	中	0.63	0.8	56	46	40	35	55	46	40	35	53	45	39	35	50	44	39	35	33
	否	0.56	1.0	62	53	46	42	60	52	46	41	58	51	45	41	56	49	45	41	39
			1.25	67	59	53	48	65	58	52	48	63	56	51	47	60	55	51	47	45
下方投影面積	cm <sup>2</sup>		1.5	70	63	57	53	69	62	57	52	66	60	56	52	64	59	55	51	49
	等価発光面積		cm <sup>2</sup>	2.0	75	69	64	60	73	68	63	59	71	66	62	59	69	64	61	58
取付高さ	器具間隔最大限		2.5	78	73	68	64	76	72	68	64	74	70	66	63	72	68	65	62	60
	横方向 (A)	縦方向 (B)	3.0	80	75	71	68	78	74	71	68	76	72	69	67	74	71	68	66	64
Hm	1.26Hm	1.26Hm	4.0	82	79	76	73	81	78	75	72	79	76	73	71	77	74	72	70	68
			5.0	84	81	78	76	83	80	78	75	80	78	76	74	78	76	75	73	71
			7.0	86	84	82	80	85	83	81	79	82	81	79	78	80	79	78	76	74
			10.0	87	86	84	83	86	85	83	82	84	83	82	80	82	81	80	79	77

