

屋内照明器具特性

| | | |
|---------|----------------|----------|
| 品番 (品名) | S P L 5 4 2 8 | |
| 光源 | LLD2000LCE1 ×4 | 531.0 lm |
| 管理番号 | K0176043(0)DR1 | |
| BZ分類 | BZ5 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-----------------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|-----|----|
| 器具効率 | 84% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 0% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 84% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 48 | 37 | 31 | 26 | 47 | 37 | 31 | 26 | 45 | 36 | 30 | 26 | 43 | 35 | 30 | 26 | 25 | |
| | 中 | 0.63 | 0.8 | 56 | 46 | 40 | 35 | 55 | 46 | 40 | 35 | 53 | 45 | 39 | 35 | 50 | 44 | 39 | 35 | 33 | |
| | 否 | 0.56 | 1.0 | 62 | 53 | 46 | 42 | 60 | 52 | 46 | 41 | 58 | 51 | 45 | 41 | 56 | 49 | 45 | 41 | 39 | |
| | | | 1.25 | 67 | 59 | 53 | 48 | 65 | 58 | 52 | 48 | 63 | 56 | 51 | 47 | 60 | 55 | 51 | 47 | 45 | |
| 下方投影面積 | cm ² | | 1.5 | 70 | 63 | 57 | 53 | 69 | 62 | 57 | 52 | 66 | 60 | 56 | 52 | 64 | 59 | 55 | 51 | 49 | |
| | 等価発光面積 | | cm ² | 2.0 | 75 | 69 | 64 | 60 | 73 | 68 | 63 | 59 | 71 | 66 | 62 | 59 | 69 | 64 | 61 | 58 | 56 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 78 | 73 | 68 | 64 | 76 | 72 | 68 | 64 | 74 | 70 | 66 | 63 | 72 | 68 | 65 | 62 | 60 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 80 | 75 | 71 | 68 | 78 | 74 | 71 | 68 | 76 | 72 | 69 | 67 | 74 | 71 | 68 | 66 | 64 | |
| Hm | 1.26Hm | 1.26Hm | 4.0 | 82 | 79 | 76 | 73 | 81 | 78 | 75 | 72 | 79 | 76 | 73 | 71 | 77 | 74 | 72 | 70 | 68 | |
| | | | 5.0 | 84 | 81 | 78 | 76 | 83 | 80 | 78 | 75 | 80 | 78 | 76 | 74 | 78 | 76 | 75 | 73 | 71 | |
| | | | 7.0 | 86 | 84 | 82 | 80 | 85 | 83 | 81 | 79 | 82 | 81 | 79 | 78 | 80 | 79 | 78 | 76 | 74 | |
| | | | 10.0 | 87 | 86 | 84 | 83 | 86 | 85 | 83 | 82 | 84 | 83 | 82 | 80 | 82 | 81 | 80 | 79 | 77 | |

