

屋内照明器具特性

品番 (品名)	S P L 5 4 2 8		
光源	LLD3020LCE1 ×4	795.0 1 m	
管理番号	K0176044 (0) DR 1		
B Z 分類	B Z 1		

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	89 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			Z C M
保守率	良	0.67	0.6	73	67	63	61	72	67	63	61	71	66	63	61	70	66	63	61	60
	中	0.63	0.8	78	73	69	67	77	73	69	67	76	72	69	67	75	71	68	66	65
	否	0.56	1.0	82	77	74	71	81	76	73	71	79	75	73	70	78	75	72	70	69
下方投影面積	等価発光面積	c m ²	1.25	84	80	77	75	84	80	77	74	82	79	76	74	80	78	75	74	72
			1.5	86	83	80	77	85	82	79	77	84	81	79	77	82	80	78	76	75
取付高さ	器具間隔最大限		2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	79	78
	横方向 (A)	縦方向 (B)	2.5	90	88	86	84	89	87	85	83	88	86	84	82	86	84	83	82	80
H m	0.41 H m	0.41 H m	3.0	91	89	87	86	90	88	87	85	89	87	85	84	87	85	84	83	81
			4.0	93	91	89	88	92	90	89	87	90	88	87	86	88	87	86	85	83
			5.0	93	92	91	90	92	91	90	89	90	89	88	87	89	88	87	86	84
			7.0	94	93	92	91	93	92	91	91	91	90	90	89	89	89	88	88	85
			10.0	95	94	93	93	94	93	93	92	92	91	91	90	90	89	89	88	86

