

屋内照明器具特性

品番 (品名)	LGB10828				
光源	LLD4000LCB1 ×1 845.0 l m				
管理番号	K0176300(0)DR1				
BZ分類	BZ2				

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	0 %	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	47 %																																																									
保守率	良 中 否	0.67	0.6	3.1	2.6	2.3	2.1	3.1	2.6	2.3	2.1	3.0	2.6	2.3	2.1	2.9	2.5	2.3	2.1	2.0																																						
		0.63	0.8	3.6	3.2	2.9	2.7	3.5	3.2	2.9	2.7	3.4	3.1	2.9	2.7	3.3	3.0	2.8	2.7	2.6																																						
		0.56	1.0	3.9	3.5	3.3	3.1	3.8	3.5	3.2	3.1	3.7	3.4	3.2	3.0	3.6	3.4	3.2	3.0	2.9																																						
			1.25	4.1	3.8	3.6	3.4	4.1	3.8	3.5	3.4	4.0	3.7	3.5	3.3	3.9	3.6	3.5	3.3	3.2																																						
下方投影面積	c m ²	1.5	4.3	4.0	3.8	3.6	4.2	4.0	3.7	3.6	4.1	3.9	3.7	3.6	4.0	3.8	3.7	3.5	3.4																																							
		2.0	4.5	4.2	4.1	3.9	4.4	4.2	4.0	3.9	4.3	4.1	4.0	3.8	4.2	4.0	3.9	3.8	3.7																																							
取付高さ	器具間隔最大限		2.5	4.6	4.4	4.2	4.1	4.5	4.3	4.2	4.1	4.4	4.3	4.1	4.0	4.3	4.2	4.1	4.0																																							
	横方向 (A)	縦方向 (B)	3.0	4.7	4.5	4.4	4.2	4.6	4.4	4.3	4.2	4.5	4.4	4.2	4.1	4.4	4.3	4.2	4.1																																							
H m	1.28 H m	1.28 H m	4.0	4.8	4.6	4.5	4.4	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.1																																							
			5.0	4.8	4.7	4.6	4.5	4.8	4.7	4.6	4.5	4.6	4.6	4.5	4.4	4.5	4.5	4.4	4.4	4.2																																						
			7.0	4.9	4.8	4.7	4.7	4.8	4.8	4.7	4.6	4.7	4.7	4.6	4.5	4.6	4.6	4.5	4.3																																							
			10.0	4.9	4.9	4.8	4.8	4.9	4.8	4.8	4.7	4.8	4.7	4.7	4.6	4.7	4.6	4.6	4.4																																							

