

|          |                             |
|----------|-----------------------------|
| 屋内照明器具特性 |                             |
| 品番 (品名)  | XLGE1006                    |
| 光源       | LLD2000NCE1 ×1 531.0 lm     |
| 管理番号     | K0176341(0)DR1              |
| BZ分類     | BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2 |

|        |         |                 |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 68%     | 天井              | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |         | 壁               | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 0%      | 床               | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 68%     | 室指数             | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.63            | 0.6         | 4.4 | 3.7 | 3.2 | 2.9 | 4.3 | 3.6 | 3.2 | 2.9 | 4.2 | 3.6 | 3.2 | 2.9 | 4.0 | 3.5 | 3.2 | 2.9 | 2.8 |
|        | 中       | 0.6             | 0.8         | 5.1 | 4.5 | 4.0 | 3.7 | 5.0 | 4.4 | 4.0 | 3.7 | 4.8 | 4.3 | 4.0 | 3.7 | 4.7 | 4.3 | 3.9 | 3.7 | 3.5 |
|        | 否       | 0.56            | 1.0         | 5.5 | 5.0 | 4.6 | 4.2 | 5.4 | 4.9 | 4.5 | 4.2 | 5.3 | 4.8 | 4.5 | 4.2 | 5.1 | 4.7 | 4.4 | 4.2 | 4.1 |
|        |         |                 | 1.25        | 5.9 | 5.4 | 5.0 | 4.7 | 5.8 | 5.3 | 5.0 | 4.7 | 5.6 | 5.2 | 4.9 | 4.7 | 5.5 | 5.1 | 4.9 | 4.6 | 4.5 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5         | 6.1 | 5.7 | 5.3 | 5.1 | 6.0 | 5.6 | 5.3 | 5.0 | 5.9 | 5.5 | 5.2 | 5.0 | 5.7 | 5.4 | 5.2 | 5.0 | 4.8 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0         | 6.4 | 6.1 | 5.8 | 5.5 | 6.3 | 6.0 | 5.7 | 5.5 | 6.2 | 5.9 | 5.6 | 5.4 | 6.0 | 5.8 | 5.6 | 5.4 | 5.3 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5         | 6.6 | 6.3 | 6.1 | 5.8 | 6.5 | 6.2 | 6.0 | 5.8 | 6.4 | 6.1 | 5.9 | 5.7 | 6.2 | 6.0 | 5.8 | 5.7 | 5.5 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0         | 6.7 | 6.5 | 6.3 | 6.1 | 6.6 | 6.4 | 6.2 | 6.0 | 6.5 | 6.3 | 6.1 | 5.9 | 6.3 | 6.2 | 6.0 | 5.9 | 5.7 |
| Hm     | 1.17Hm  | 1.17Hm          | 4.0         | 6.9 | 6.7 | 6.5 | 6.3 | 6.8 | 6.6 | 6.4 | 6.3 | 6.6 | 6.5 | 6.3 | 6.2 | 6.5 | 6.3 | 6.2 | 6.1 | 6.0 |
|        |         |                 | 5.0         | 7.0 | 6.8 | 6.7 | 6.5 | 6.9 | 6.7 | 6.6 | 6.5 | 6.7 | 6.6 | 6.5 | 6.4 | 6.6 | 6.5 | 6.4 | 6.3 | 6.1 |
|        |         |                 | 7.0         | 7.1 | 7.0 | 6.8 | 6.7 | 7.0 | 6.9 | 6.8 | 6.7 | 6.8 | 6.7 | 6.7 | 6.6 | 6.7 | 6.6 | 6.5 | 6.5 | 6.3 |
|        |         |                 | 10.0        | 7.2 | 7.1 | 7.0 | 6.9 | 7.1 | 7.0 | 6.9 | 6.8 | 6.9 | 6.8 | 6.8 | 6.7 | 6.8 | 6.7 | 6.7 | 6.6 | 6.4 |

