

屋内照明器具特性

品番 (品名)	XLGE1128	
光源	LLD3020VCE1 ×1	795.0 lm
管理番号	K0176345(0)DR1	
BZ分類	BZ1	

器具効率	89%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	89%	床	10%				10%				10%				10%				0%	
室指数	照明率 (×0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	87	88	90	92	93	94	94	95	95
	等価発光面積		cm ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	88	88	88	88	88	88	88	88	88
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
Hm	0.41Hm	0.41Hm	4.0	5.0	7.0	10.0	94	94	94	94	94	94	94	94	94	94	94	94	94	94

