

屋内照明器具特性	
品番 (品名)	XAD11004K
光源	LLD20004CQ1 ×1 531.0 lm
管理番号	K0175550 (0) DR 1
BZ分類	BZ4 / 0.7 / BZ3

器具効率		83 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29				
			0.63	0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39				
			0.56	1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45				
				1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51				
下方投影面積 等価発光面積		cm ² cm ²		1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55				
				2.0	77	72	68	65	76	71	68	64	74	70	66	64	72	68	65	63	61				
				2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65				
				3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68				
Hm	1.25Hm	1.25Hm		4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71				
				5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73				
				7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76				
				10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78				

