

屋内照明器具特性

品番 (品名)	L G W 4 1 0 0 2				
光源	LLD4000MLCE1 ×1 845.0 l m				
管理番号	K0176340 (0) DR 1				
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2				

器具効率	59 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	0 %																					
下方光束	59 %																					
		室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.63	0.6	3.8	3.2	2.8	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	3.5	3.1	2.8	2.5	2.4		
	中	0.6	0.8	4.4	3.9	3.5	3.2	4.4	3.8	3.5	3.2	4.2	3.8	3.5	3.2	4.1	3.7	3.4	3.2	3.1		
	否	0.56	1.0	4.8	4.3	4.0	3.7	4.7	4.3	3.9	3.7	4.6	4.2	3.9	3.7	4.5	4.1	3.9	3.6	3.5		
			1.25	5.1	4.7	4.4	4.1	5.1	4.7	4.3	4.1	4.9	4.6	4.3	4.1	4.8	4.5	4.2	4.0	3.9		
下方投影面積	c m ²		1.5	5.3	5.0	4.7	4.4	5.3	4.9	4.6	4.4	5.1	4.8	4.6	4.4	5.0	4.7	4.5	4.3	4.2		
等価発光面積	c m ²		2.0	5.6	5.3	5.0	4.8	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.9	4.7	4.6		
取付高さ	器具間隔最大限		2.5	5.8	5.5	5.3	5.1	5.7	5.4	5.2	5.1	5.5	5.3	5.2	5.0	5.4	5.2	5.1	4.9	4.8		
	横方向 (A)	縦方向 (B)	3.0	5.9	5.6	5.5	5.3	5.8	5.6	5.4	5.2	5.6	5.5	5.3	5.2	5.5	5.4	5.2	5.1	5.0		
H m	1.17 H m	1.17 H m	4.0	6.0	5.8	5.7	5.5	5.9	5.8	5.6	5.5	5.8	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.2		
			5.0	6.1	5.9	5.8	5.7	6.0	5.9	5.8	5.6	5.9	5.8	5.7	5.6	5.7	5.6	5.6	5.5	5.3		
			7.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.8	5.8	5.7	5.6	5.5		
			10.0	6.2	6.2	6.1	6.0	6.2	6.1	6.0	6.0	6.0	6.0	5.9	5.9	5.9	5.8	5.8	5.8	5.6		

