

屋内照明器具特性

品番 (品名) **LGW41002**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176346(0)DR1**

BZ分類 **BZ1**

器具効率	87%	天井	80%				70%				50%				30%				0%
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	87%	床	10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM

保守率	良	0.63	0.6	0.56	0.6	74	68	65	63	73	68	65	63	72	68	65	63	71	67	65	63	62	
	中	0.6	0.6	0.56	0.8	79	74	71	69	78	74	71	69	77	73	70	68	75	72	70	68	67	
	否	0.56	1.0	82	78	75	73	81	77	74	72	79	76	74	72	78	76	73	72	71	71	71	
下方投影面積	等価発光面積	cm ²	cm ²	1.25	84	81	78	76	83	80	78	76	82	79	77	75	81	78	76	75	74		
				1.5	86	83	80	78	85	82	80	78	83	81	79	77	82	80	78	77	76	76	
取付高さ	器具間隔最大限		H _m	0.41H _m	0.41H _m	2.5	89	87	85	84	88	86	85	83	86	85	83	82	85	84	82	81	80
	横方向 (A)	縦方向 (B)				3.0	90	88	86	85	89	87	86	85	87	86	85	84	86	84	83	83	81
H _m	0.41H _m	0.41H _m	4.0	91	89	88	87	90	89	88	86	88	87	86	85	87	86	85	84	82	82	82	
			5.0	92	90	89	88	91	90	89	88	89	88	87	86	87	86	85	87	86	85	83	83
			7.0	92	91	91	90	91	90	90	89	89	88	88	88	87	87	86	84	84	84	84	
			10.0	93	92	92	91	92	91	91	90	90	89	89	89	88	88	87	87	85	85	85	

