

# 屋内照明器具特性

品番 (品名)	LGW40100	
光源	LLD2020MLCE1 ×1	460.0 lm
管理番号	K0176349(0)DR1	
BZ分類	BZ1	

器具効率	89%	天井	80%				70%				50%				30%				0%										
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%									
下方光束	89%	床	10%				10%				10%				10%				0%										
室指数	照明率 ( X0.01 )																			ZCM									
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6									
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6									
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56									
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																		
		cm <sup>2</sup>	86	88	90	92	92	93	94	94	95	95																	
取付高さ	器具間隔最大限																												
	横方向 (A)	縦方向 (B)																											
Hm	0.41Hm	0.41Hm																											

